

In the Claims:

Please amend claim 1, and add new claims 60-87 as follows:

1. (Currently Amended) A carrier for supporting a microelectronic substrate relative to a planarizing medium during planarization of the microelectronic substrate, the carrier comprising:

a support member; and

a flexible, compressible membrane adjacent to the support member, the membrane having a first portion with a first thickness and a second portion with a second thickness greater than the first thickness, the first portion of the membrane being aligned with a first part of the microelectronic substrate when the membrane engages the microelectronic substrate, the second portion of the membrane being aligned with a second part of the microelectronic substrate when the membrane engages the microelectronic substrate, the substrate being held stationary with respect to the membrane as the substrate is moved relative to the planarizing medium.

2-3. (Cancelled)

2/
4. (Original) The carrier of claim 1 wherein the membrane has a first surface facing a generally flat surface of the support member and a second surface facing opposite the first surface toward the microelectronic substrate when the membrane engages the microelectronic substrate, the first surface being generally in direct contact with the flat surface of the support member.

3/
5. (Original) The carrier of claim 1 wherein the membrane has a generally circular planform shape and the first and second portions of the membrane are annular with the first portion disposed radially inwardly from the second portion.

~~46.~~ (Original) The carrier of claim ~~5~~³ wherein the first and second portions of the membrane are concentric.

~~57.~~ (Original) The carrier of claim 1 wherein the membrane has a generally circular planform shape and the first and second portions are annular with the second portion disposed radially inwardly from the first portion.

~~68.~~ (Original) The carrier of claim 1 wherein the membrane includes a membrane material and the membrane is formed by injecting the membrane material into a mold.

~~79.~~ (Original) The carrier of claim 1 wherein the membrane includes at least one of neoprene and silicone.

~~810.~~ (Original) The carrier of claim 1 wherein the first thickness of the membrane is approximately 0.030 inches.

~~9 11.~~ (Original) The carrier of claim 1 wherein a ratio of the second thickness of the membrane to the first thickness of the membrane is less than approximately two.

~~10 12.~~ (Original) The carrier of claim 1 wherein the first and second portions are adjacent to each other.

~~11 13.~~ (Original) The apparatus of claim 1 wherein the first and second portions of the membrane are radially disposed relative to each other and an intermediate thickness of the membrane varies in a generally continuous manner between the first thickness and the second thickness.

~~14-59.~~ (Cancelled)

82
12/60. (New) A carrier for supporting a microelectronic substrate relative to a planarizing medium during planarization of the microelectronic substrate, the carrier comprising:
a support member; and
a flexible, compressible membrane having an upper ply adjacent to the support member, and a lower ply depending downwardly from the upper ply, the lower ply having a first portion with a first thickness and a laterally spaced apart second portion with a second thickness greater than the first thickness, the first portion of the lower ply being aligned with a first part of the microelectronic substrate and applying a first force to the substrate when the lower ply engages the microelectronic substrate, the second portion of the lower ply being aligned with a second part of the microelectronic substrate and applying a second force different from the first force when the lower ply engages the microelectronic substrate, the first and second portions simultaneously contacting the microelectronic substrate when the lower ply engages the substrate, the substrate being held stationary relative to the membrane as the substrate is moved relative to the planarizing medium.

13/61. (New) The carrier of claim ¹²60 wherein the support member has a generally circular planform shape.

14/62. (New) The carrier of claim ¹²60 wherein the upper ply has a generally circular planform shape and the lower ply has a generally annular shape with the first portion disposed radially inwardly from the second portion.

15/63. (New) The carrier of claim ¹²60 wherein the upper ply has a generally circular planform shape and the lower ply has a generally annular shape with the second portion disposed radially inwardly from the first portion.

16/64. (New) The carrier of claim ¹²60 wherein a ratio of the second thickness of the lower ply to the first thickness of the lower ply is less than approximately two.

17/65. (New) The carrier of claim ¹²60 wherein the first thickness of the lower ply is approximately 0.030 inches.

18/66. (New) The carrier of claim ¹²60 wherein the upper ply includes at least one of neoprene and silicone.

19/67. (New) The carrier of claim ¹²60 wherein the lower ply includes at least one of neoprene and silicone.

20/68. (New) The carrier of claim ¹²60 wherein the upper ply and the lower ply are formed from a compressible material by injecting the compressible material into a mold.

21/69. (New) The carrier of claim ¹²60 wherein the upper ply and the lower ply are adhesively attached.

22/70. (New) The carrier of claim ¹²60 wherein the first and second portions of the lower ply are radially disposed relative to each other and an intermediate thickness of the lower ply varies in a generally continuous manner between the first thickness and the second thickness.

23/71. (New) A carrier for supporting a microelectronic substrate relative to a planarizing medium during planarization of the microelectronic substrate, the carrier comprising:

a support member; and

a flexible, compressible membrane adjacent to the support member, the membrane having a first portion with a first thickness and a laterally spaced apart second portion with a second thickness greater than the first thickness, the first portion of the membrane being configured to apply a first force to the substrate when the membrane engages the microelectronic substrate, the second portion of the membrane being configured to apply a second force to the substrate when the membrane engages the microelectronic substrate, the second force being different from the first force and the first and second portions simultaneously contacting the

microelectronic substrate when the membrane engages the substrate, the substrate being held stationary relative to the membrane as the substrate is moved across the planarizing medium.

²⁴₇₂ (New) The carrier of claim ²³₇₁ wherein the support member has a generally circular planform shape.

²⁵₇₃ (New) The carrier of claim ²³₇₁ wherein a ratio of the second thickness of the membrane to the first thickness of the membrane is less than approximately two.

²⁶₇₄ (New) The carrier of claim ²³₇₁ wherein the first thickness of the membrane is approximately 0.030 inches.

²⁷₇₅ (New) The carrier of claim ²³₇₁ wherein the membrane is comprised of at least one of neoprene and silicone.

²⁸₇₆ (New) The carrier of claim ²³₇₁ wherein the membrane includes at least one of neoprene and silicone.

²⁹₇₇ (New) The carrier of claim ²³₇₁ wherein the membrane is formed from a compressible material by injecting the compressible material into a mold.

³⁰₇₈ (New) A carrier for supporting a microelectronic substrate relative to a planarizing medium during planarization of the microelectronic substrate, the carrier comprising:

a support member; and

a flexible, compressible membrane having an upper ply adjacent to the support member, and a lower ply depending downwardly from the upper ply, the lower ply having a first portion with a first thickness and a laterally spaced apart second portion with a second thickness greater than the first thickness, the first portion of the lower ply being configured to apply a first force to the substrate when the substrate is aligned with the lower ply and the second portion being configured to apply a second force to the substrate when the substrate is aligned with the

lower ply, the first and second portions simultaneously contacting the substrate, the substrate being held stationary with respect to the lower ply as the substrate is moved across the planarization medium

31
~~79~~. (New) The carrier of claim ~~78~~³⁰ wherein the support member has a generally circular planform shape.

32
~~80~~. (New) The carrier of claim ~~78~~³⁰ wherein the upper ply has a generally circular planform shape and the lower ply has a generally annular shape with the first portion disposed radially inwardly from the second portion.

33
~~81~~. (New) The carrier of claim ~~78~~³⁰ wherein a ratio of the second thickness of the lower ply to the first thickness of the lower ply is less than approximately two.

34
~~82~~. (New) The carrier of claim ~~78~~³⁰ wherein the first thickness of the lower ply is approximately 0.030 inches.

35
~~83~~. (New) The carrier of claim ~~78~~³⁰ wherein the upper ply includes at least one of neoprene and silicone.

36
~~84~~. (New) The carrier of claim ~~78~~³⁰ wherein the lower ply includes at least one of neoprene and silicone.

37
~~85~~. (New) The carrier of claim ~~78~~³⁰ wherein the upper ply and the lower ply are formed from a compressible material by injecting the compressible material into a mold.

38
~~86~~. (New) The carrier of claim ~~78~~³⁰ wherein the upper ply and the lower ply are adhesively attached.

³⁹
87.

³⁰
78.

(New) The carrier of claim 78, wherein the first and second portions of the lower ply are radially disposed relative to each other and an intermediate thickness of the lower ply varies in a generally continuous manner between the first thickness and the second thickness.--
